

Especificaciones Técnicas

Camara Cant: 108	Camara Analogica
	Tipo domo antivandalico
	Weather Proof: IP66
	700TVL high resolution
	Day& Night: IR cut filter with auto switch
	Lente: 2.8-12 mm @ F1.4. Angle of view: 80° - 27.2°
DVR Cant: 54	Analog Video Input: 4-ch. Aviation plug (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
	Audio Input: 4-ch. Aviation plug (linear electrical level, 1 KΩ)
	Video Output: 1-ch CVBS video output, aviation plug (1.0 Vp-p , 75 Ω).
	Resolution: PAL: 704 × 576, NTSC: 704 × 480
	Audio Output: 1-ch, aviation plug (linear electrical level, 600 Ω)
	Video compression: H.264
	Audio Compression: G.711
	Conexión con HDD/SSD SATA de 2.5 pulgadas y tarjeta SD/SDHC
	Modulo 3G incorporado para emitir en tiempo real
	Modulo WiFi incorporado para emitir en tiempo real
	Chasis de aluminio
Disco Rigido Cant: 54	HDD o SSD SATA
	Al menos 500GB
Conversor de tensión Cant: 54	Input: 20-30 VDC
	Output: 13.8 VDC
	Amps: 12 Amps